

FLEX

ROBOTIC SAMPLING PLATFORM

*The **easiest** software interface
you'll ever use*



- User friendly drag-and-drop functionality
- No expensive software upgrades to purchase
- Maximize GC productivity through overlapping prep routines
- Simplified menu options that can be easily edited with no need for macro programming
- Unsurpassed agility with line-by-line editing capability without sequence interruption
- Real-time run-status screen enables up to the minute analyst confidence
- Automated calibration of tray and accessories minimizes traditional set-up time
- .CSV Sequence integration with Chemstation and OpenLAB

NEW *Intuitive Software*

No more struggling with complicated macros

EST 
analytical *Rely On Us* 

FLEX

ROBOTIC SAMPLING PLATFORM

*The **easiest** software interface
you'll ever use*

Method Routines

Flex Method Routines	Method Type		
	Liquid	Headspace	SPME
Rinse	✓		
Wait	✓	✓	✓
Air Volume	✓	✓	
Gap Sample	✓		
Solvent Plug	✓		
Standard Addition	✓	✓	
Single Port Injection	✓		
Multi-Port Injection	✓		
Incubate/Agitate	✓	✓	✓
Sample Injection		✓	
Sample Fill		✓	
Extraction			✓
Desorption			✓
Sweep Needle	✓	✓	
Condition Fiber			✓
Sample Prep.	✓	✓	✓
Gas Standard Addition		✓	

Specifications

Power

- 100-240 VAC, 50/60 Hz, 3-1A

Available Options

- **Liquid Injection Option**
 - 105 position 2mL tray
 - Syringe and syringe holder
- Tray and other stations
 - 2mL tray; 105 position (up to 4 trays)
 - 10mL-20mL tray; 32 position
 - Custom trays available
- 10mL Rinse/Waste station – 4 positions
- 100mL Rinse/Solvent – 2 positions with a waste port
- Mounting hardware available for various GC platforms
- **Headspace Option** – Consisting of
 - Incubation/Agitation Station
 - 6 position vial holder for 20 mL headspace vials
 - Capable of holding 2mL and 10mL vials with inserts
 - Heating capability up to 200°C
 - Agitation of all 6 positions orbital from 120-750 rpm or oscillation at 190Hz
 - Syringe Heater Accessory
 - To accommodate 1ml or 2.5 ml headspace syringes
 - Heating Capability up to 150 °C
- **SPME Option** – Consisting of
 - Needle/Fiber Conditioning Station
 - Single position fiber conditioner with sweep gas
 - Heating Capability up to 350 °C
 - Single magnet mixer
 - SPME fiber holder