

environmental

ambient pollution analyzers and calibration systems

T [å^ |ÁG€G€-EXP Ú[ˈcæà |^ÁZ^¦ [ÁCŒ ÁSource

Uç^¦çã\

V@ÁT[å^|ÁGEGE-EXPÁā ÁæÁ|[¦œàà|^Áq[*!&^Áq[;k&l^æ) ÊÉ&|^ÁæálÁ&^•ã*}^åÁq[Á; ^^cÁæá, ã&^Áæ) *^Á; Æ $^{1}^{3}$ 4 6 zero æālÁ[| Ásælæa|æaa] } Án • c^{ • Át Á * | * ^ ÁsælÁt | Á ^ | { ^ æaa] } Át ç^} • Éls@ Át ael Á æss æ* ^ Á a ^ Ásæl å Á . ^ã @Á, æ\^Ás@ÁT[å^|ÁΘ€Θ€-EXPÁs@Á,\^-^\;\^åÁ&@,&XÁ[¦Á&N|åÁæ),åÁsĕ åãAÁ,^\;•[}}^|Á;æÁ, ^||Á æ ¼] ^ | ææð * Á } çã [} { ^ } o Á ão @Áã ã ° å Áà ^ } & @Á] æ& ^ È

V@ÁT[å^|ÁG€G€-EXPÁ•^•Ása)Ásjc^¦}æþÁ,^¦{ ^ææã[}Ási^ã;*Ár^•c^{A[¦Á;[ãrč¦^Á^{[çæþÁsa)åÁsiÁ • ` &@Áse Ás@Ás; c^¦} æþÁsæðà[} Á; [} [¢ãå^ÁÇÔU DÍ;¢ãåã ^¦Á;¦ÁnternalÁ@å¦[&æðà[}ÁQPÔDÍ;¢ãåã ^¦Á ~ ¦c@¦Ás@ÁT[å^|ÁG€G€-EXPqÁs|^æ)ÁsaálÁsæ)æàãããã•È

W•^¦ÁÓ^}^ã•

Ùã[]|^Ándæaaf@dË[¦;æ+åÁs[}d[|•Áæ+|[;Án[&æ+An[]^¦æaā[}Á+[{Ás@^Á+[}o4)æ-}^|£Á;ās@Ás@^Án[]aā[}Án[Á •^o/sc@^Aj`;*^Ad-^``^}&^Ase) å.Asi;læsaj;}A[;Aj[]caj `{Aj^-;-[;{æ)&^EXOEååaaj;}æ|j^EXs@^A;}aóA æčd[{ææã8æ4|^Á妿ã;•Á([ãcč¦^Áæ)åÁ,¦^••*¦ã^åÁæãÁ;}&^Á,[¸^¦^åÁå[¸}È

The Model 2020-EXP is a split chassis design that has a removable Control/Cleanup module and a separate removable pump module that can be used together or independently. The split design allows the overall weight of the unit to be distributed for users to easily carry inside of shelters or locations that are difficult to access. All modules can be stored for shipment inside of the provided transport case that has a telescopic handle and wheels.

aa) ^ ÁÚ aaa aj Ásaapaa | aag | HÁV @a Ár ¢&| * • āç ^ Ár aas ' | ^ Ásap| [• Ás@ Á • ^ | Ág Á cad cósap å Ár dg] Ás@ Á } ān Ásae Á }^^å^åÁ[Áæ[ãåÁ}}^&^•æf^Á*} Áæ] ^•LÁB,&|^æ-ā,*Á,*{] Áã^Áæ} åÁå^&|^æ-ā,*Á^|ç28^Á ã c⁴¦çæ•È

Ùæ) åæ\åÁØ^æc`¦^•

- ▶Ùæ) 忦åÁ30ÁŠÚTÁOÁ\$5ÁÚÙÕ
- Pressure or Vacuum mode for pump module
- Condensate/purge valving for moisture removal
- ▶ Automatic purge frequencies
- ▶Ø{[} oÁ, æ}^|Á, [*] o^å Áæåb œà|^Á, !^••* | A^* | æ{ | with pressure gauge
- ▶P`¦*^Á, ã&.@
- ▶ Q c^\ } ædÁ\^\ { ^æda } Á&\^^\
- ▶T^åãæÁsæ)ãœ'\•Á;¦Á^{ [çæ)Á,-ÁÞUÉÁÞU,ÉÁU,ÉÁU,ÉÁU,ÉÉP,Ù
- Rugged top mounted carrying handles
- ▶Dew point Less than -20°C
- ▶1/4" outlet ports



U] cai } aal/AØ^aec \^•

CO Oxidizer

Pydrocarbon Oxidizer

Ö^, ÁÚ[ã, cÁQ å ã&æ [¦Á

CO2 Scrubber

1 x Ethernet: 10/100Base-T

1 x RS232 (300-115,200 baud)

MODBUS Protocol Support

Ú 4 LO ZO Ô Ô Ô Ô Ú Ú

Ù]^8ãã8æã}}•Á`àb\8oÁ[Á&@;*^Á;ã@`oÁ[æ&^

CEDÜÁÛWOEŠOVŸ

ٜ åæåå Å }ãc

cææaan cæða Ald ¢æða a hlá

NO, ÞUxĐPU ĐU ĐU ĐĐ CÙÁL€Đ25Á] à Ùæ) 忦åÁ`}ãóĄ ĐÔUÁ NO, ÞUxÉÞUGÐUĻÉÐUGÐPGÙÁL€Ð2ÍÁ,] àÉA

ÔUÁLÁÁ1à

Ùcza) åzelåÁ}ãoÁ,ãoÓÁ Internal ÁP Ó Á& ææð ° cæð Á [¢ãåã^¦

NO, ÞUxÊÁÞU JÁÚU JÁP JÚ, NH3Á Ł€ĖD2ĺÁ,]àÉÁ

P^å¦[&æåà[}ÁmÁÈG€Ál]à,

CO < 5 ppb

T Ò ÔP Œ Đ Ó Œ Š

P^at @: Y aac@Ö^1 c@

11/48/EÁQ27.9/48{ DÁXÁ17/48/EÁQ43.1/48{ DÁ

21 ȀÁ§ ÈÁÇ53.3Á&{ D

OFc^\at ^AY ^a @A 30Áà•ÁŒ3.6Á* Dmodules in case 15

> lbs (13.6 kg) pump module 10 lbs (13.6 kg) Control/Cleanup module 40

lbs (13.6 kg) w/HC Oxidizer

ÒŠÒÔVÜ Ø Ø Ø

Ùcz aza åÁ

98-132 VAC, 50/60HZ

U] dai } æ

FJÎËĞÎIÁKOÐÔÊÃEÐ΀ÁP:

Sabio Environmental, LLC 21 Cypress Blvd., Suite 1130 Round Rock, TX 78665 512.869.0544 sales@sabio.com www.sabio.com